

OVERLOCK STITCH

700K

747 K - 514 M 2 - 2 4 / VT / DKK□

機種別 Model
 K 一般型高速包縫/安全縫
 General Type High Speed
 Overlock/ Safety Stitch

送具型式
 Feed dog type

配件
 Device

線數
 Thread numbers

737 : 3T
747 : 4T
757 : 5T
767 : 6T

縫合方式
 Sewing types

503	
504	
505	
512	
514	
516	
514 + 401	

針距
 Needle gauge

包邊寬度
 Overedge width

車縫布料
 Sewing fabric

F 輕薄布料 Fine weight fabric
L 薄布料 Light weight fabric
M 中厚布料 Medium weight fabric
H 厚布料 Heavy weight fabric
X 特厚布料 Extra heavy weight fabric

直驅伺服馬達
 Direct-drive servo motor

DKK□ 700K/700KST/700KS/700KT型直驅電控組
 Direct-Drive Servo Motor for 700K/700KST/
 700KS/700KT
 請參閱 P.49 Detail on Page.49

Energy saving 節能省電

Low temperature rising 溫升低

Good insulation 絕緣良好



700K/DKKU1

700K 系列包縫機配備直驅伺服馬達

Overlock machine with Direct-Drive Servo Motor



Feature 特點

- | | |
|--------------------|---|
| 1. 馬力強，同時又節能省電 | 1. Powerful while energy saving. |
| 2. 溫升高，安全絕緣良好 | 2. Low temperature rising, and safety with good insulation. |
| 3. 與 700K 之規格與配件相容 | 3. Compatible with 700K in specifications and accessories. |



控制器 Controller	配件 Device	電眼切刀 Sensor Trimmer	抬壓腳 Presser Foot Lifter	吸風集塵組 Air Suction Set	操作面板 Control Panel	針板 Needle Plate
DKKU□-0 經濟型 Economic Type	700K 相容配件 700K Compatible device		選配 / Optional TUA-32K	選配 / Optional TUA-31, 32K		標準型 Standard
DKKU□-1 多功能型 Multi-function Type	ECA-U		氣動 Pneumatic	氣動 Pneumatic		標配 Included
	ECB-U	電動 Electric	電動 Electric			
	VTE-U	吸風切線 Suction Trimmer	氣動 Pneumatic			
	CTE	吸風切線 Suction Trimmer	氣動 Pneumatic			



700K SERIES FEATURES



密封式直接傳動針棒專利機構

- 密閉針棒室，防塵防鏽汗滲入，避免漏油
- 縫製動能沿針棒運動方向直接傳達，有效提升縫紉高速化及耐久性；避免連杆式針棒之傳動耗損

Sealed type direct drive needle bar mechanism

- Dust free and oil-leakage-free are due to entirely sealed needle bar section design.
- Direct drive needle bar system leads to high speed and long durability.No driving loss of connecting-rod-drive needle bar system.



全新強制供油/回油及濾油系統

針棒，上勾針機構採用強制給油及全密閉式真空回油機構，完全排除以油線供油或滴落式供油產生問題

Active lubrication system

Needle bar and upper looper mechanisms are applied active oil supply and entirely sealed vacuum oil return system. The new system exceeds the traditional oil supply of rope type and dropping type.



專利雙刮雙唇式送具防漏設計

除雙刮板外又新增雙唇式刮板，阻油防油效果較原有雙刮板設計效果更佳

Patented feed dog mechanism oil proof system

New double-lip type wiper is added to support the original double wiper. Oil proof function is upgraded.



直接傳動式送具機構

直接傳動可防止差動輸送過度，縫紉更準確順暢，不用調整差動齒，避免連杆式送具之傳動耗損

Direct drive feeding mechanism

Direct drive mechanism prevents overdoing of differential feeding. No need to adjust the differential feed dog. No drive loss of connecting rod and type feeding mechanism.



新型切刀機構

刀座軸心低式設計，可防止面料回推現象，使面料切斷時不會產生捲邊現象

New fabric trimmer mechanism

Low axis knife holder prevents cloth rolls up after trimming.



專利一體化內藏式照明 (選購)

LED燈內藏一體化設計，穿線、目視操作方便，整體美觀

Patented integrated built-in lighting (Optional)

- Integrated built-in LED light design is artistic and user friendly.



可選配專用送具車縫超薄布料

例如: D201與H201標準品齒距為1.6mm ; D201A與H201A選購品齒距為0.8mm ; D201B與H201B選購品齒距為1.0mm

Feed dog for extra light weight fabric (Optional)

E.g.: D201 & H201(standard): Teeth spacing 1.6mm; D201A & H201A(optional): Teeth spacing 0.8mm; D201B & H201B(optional): Teeth spacing 1.0mm.



可選配短壓具舌車縫厚布料或長壓具舌車縫薄布料，讓車縫線跡更加完美

Optional presser foot fingers for better sewing performance: short finger for heavy fabric, long finger for light fabric.








更多便於使用的特點...

- 免開蓋針高調整，操作便利
- 下勾針座前後微調機構，維修省時簡易
- 環縫微調機構，開後蓋調粗細針，迅速省時
- 針板出線槽設計，包縫/環縫出線線圈更柔軟完美
- 車頭高度達5cm使進出布更加方便

More user friendly features:

- Needle bar height adjustment without opening machine.
- Lower looper holder fine tune mechanism.
- Chainstitch fine tune mechanism: Open the rear cover to adjust stitch length easily.
- Needle plate thread groove leads to perfect loop.
- 5 cm height sewing area offers better cloth movement.

															Remark
				mm	mm	mm	mm	mm	mm	mm	mm	mm	S.P.M. (Max.)		
737K-503M2-04	1	3	-	4	0.7-2	3.6	6	DCX27#11	7500	A					
737K-504F1-04	1	3	-	4	0.7-2	3.6	6	DCX27#11	7500						
737K-504M2-04	1	3	-	4	0.7-2	3.6	6	DCX27#11	7500						
737K-504M3-04	1	3	-	4	0.7-2	3.6	6	DCX27#11	7500	B					
737K-504M3-05	1	3	-	5	0.7-2	3.6	6	DCX27#11	7500	B					
747K-514F1-24	2	4	2	4	0.7-2	3.6	5.5	DCX27#11	7500						
747K-512M1-25	2	4	2	5	0.7-2	3.6	5.5	DCX27#11	7500	D					
747K-512M1-34	2	4	3	4	0.7-2	3.6	5.5	DCX27#11	7500	D					
747K-514M2-24	2	4	2	4	0.7-2	3.6	5.5	DCX27#11	7500	C					
747K-514M2-25	2	4	2	5	0.7-2	3.6	5.5	DCX27#11	7500	C					
747K-514M2-28	2	4	2	8	0.7-2	3.6	4	DCX27#11	7500						
747K-514M4-23	2	4	2	3	0.7-2	3.6	6	DCX27#11	7500						
757K-516L1-24	2	5	2	4	0.7-2	3.6	6	DCX27#14	7500						
757K-516L1-35	2	5	3	5	0.7-2	3.6	6	DCX27#14	7500						
757K-516M2-35	2	5	3	5	0.7-2	3.6	6	DCX27#14	7500						
757K-516M2-55	2	5	5	5	0.7-2	3.6	6	DCX27#14	7500						
767K-516M2-324	3	6	3+2	4	0.7-2	3.6	6	DCX27#11	7000	E					
767K-516M2-524	3	6	5+2	4	0.7-2	3.6	6	DCX27#11	7000	E					
737K-504F1-04/DKK□	1	3	-	4	0.7-2	3.6	6	DCX27#11	7500						
737K-504M2-04/DKK□	1	3	-	4	0.7-2	3.6	6	DCX27#11	7500						
737K-504M3-04/DKK□	1	3	-	4	0.7-2	3.6	6	DCX27#11	7500	B					
737K-504M3-05/DKK□	1	3	-	5	0.7-2	3.6	6	DCX27#11	7500	B					
747K-514F1-24/DKK□	2	4	2	4	0.7-2	3.6	5.5	DCX27#11	7500						
747K-512M1-25/DKK□	2	4	2	5	0.7-2	3.6	5.5	DCX27#11	7500	D					
747K-512M1-34/DKK□	2	4	3	4	0.7-2	3.6	5.5	DCX27#11	7500	D					
747K-514M2-24/DKK□	2	4	2	4	0.7-2	3.6	5.5	DCX27#11	7500	C					
747K-514M2-25/DKK□	2	4	2	5	0.7-2	3.6	5.5	DCX27#11	7500	C					
747K-514M2-28/DKK□	2	4	2	8	0.7-2	3.6	4	DCX27#11	7500						
747K-514M4-23/DKK□	2	4	2	3	0.7-2	3.6	6	DCX27#11	7500						
757K-516L1-24/DKK□	2	5	2	4	0.7-2	3.6	6	DCX27#14	7500						

										Remark
757K-516L1-35/DKK□	2	5	3	5	0.7-2	3.6	6	DCX27#14	7500	
757K-516M2-35/DKK□	2	5	3	5	0.7-2	3.6	6	DCX27#14	7500	
757K-516M2-55/DKK□	2	5	5	5	0.7-2	3.6	6	DCX27#14	7500	
767K-516M2-324/DKK□	3	6	3+2	4	0.7-2	3.6	6	DCX27#11	7000	E
767K-516M2-524/DKK□	3	6	5+2	4	0.7-2	3.6	6	DCX27#11	7000	E



737K-504M3-04

747K-514M2-24

757K-516M2-35

767K-516M2-324



504



514



516




401+514

一般包縫

適用於特薄至中厚布料之包縫

GENERAL SEAMING

For regular seaming on light to medium fabric.



Remark

- A: 上勾針為盲勾針
- B: 單排送具
- C: 適用於薄至中厚布料之包縫
- D: 用於薄至中厚布料之一般縫合 (假五線)
- E: 適用於薄至中厚布料之一般縫合 · 適合小量生產的打樣室或工作室選用 · 可由勾針及針之變換車縫出5種不同的縫合方式 (504,514,516, 401, 514+401)

- A: Upper looper is blind looper
- B: Single row feed dog
- C: For regular seaming on light to medium fabric.
- D: Mock 516 seaming
For regular seaming on light to medium fabric.
- E: For regular seaming on light to medium fabric.
Specially suitable for small production workshop, and fashion design studio. A variety of five different sewing types by changing number of needle and looper. (504, 514, 516, 401, 514+401).

選購配件 OPTIONAL DEVICE

VT, CSA, CSB, TUB

K2

										Remark
737K-504F2-02/GAL	1	3	-	2	0.7-2	3.6	5.5	DCX27#9	7500	A
737K-504F1-15	1	3	-	1.5	0.7-2	3.6	5.5	DCX27#9	7500	B
737K-504M1-15	1	3	-	1.5	0.7-2	3.6	6	DCX27#9	7500	C
737K-504F2-02/GAL/DKK□	1	3	-	2	0.7-2	3.6	5.5	DCX27#9	7500	A
737K-504F1-15/DKK□	1	3	-	1.5	0.7-2	3.6	5.5	DCX27#9	7500	B
737K-504M1-15/DKK□	1	3	-	1.5	0.7-2	3.6	6	DCX27#9	7500	C



737K-504F2-02/GAL




737K-504F1-15



737K-504M1-15





A



B



C



Remark

細包縫










- A.適用於特薄布料之捲邊細包縫 (荷葉邊) 例如: 手帕、禮服等
- B.適用於特薄布料之捲邊細包縫 (手帕邊包縫) 例如: 絲綢類布料之手帕、禮服等
- C.適用於薄至中厚布料之細包縫 (手帕邊包縫) 例如: 手帕、禮服等

FINE EDGING

- A. For fine edging on extra light knit fabric. The presser foot is with fine folding function. (falbala edging)
Eg: Handkerchief & dress...etc.
- B. For fine edging on extra light knit fabric. The presser foot is with fine folding function. (handkerchief edging)
Eg: Handkerchief & dress of silk fabric...etc.
- C. For fine edging on light to medium fabric. (handkerchief edging)
Eg: Handkerchief & dress ...etc.

選購配件 OPTIONAL DEVICE
VT, CSA, CSB, TUB

K3

									
747K-514M2-24/TG	2	4	2	4	0.7-2	3.6	6	DCX27#11	7500
747K-514M2-25/TG	2	4	2	5	0.7-2	3.6	6	DCX27#11	7500
747K-514M2-24/TG/DKK□	2	4	2	4	0.7-2	3.6	6	DCX27#11	7500
747K-514M2-25/TG/DKK□	2	4	2	5	0.7-2	3.6	6	DCX27#11	7500



747K-514M2-24/TG/EC



肩帶包縫


適用於針織衣服如T恤·毛衣等之肩部多車一條織帶·可防止衣服肩部變形

TAPE INSERTING

For sewing a woven tape onto the shoulder of knitwear such as T-shirt or sweater etc., to prevent abnormal stretching.

選購配件 OPTIONAL DEVICE
EC, LFA, LS

K4

									
737K-505F1-04	1	3	-	4	0.7-2	3.6	6	DCX27#9	7500
737K-505F1-04/DKK□	1	3	-	4	0.7-2	3.6	6	DCX27#9	7500



737K-505F1-04



KU60-A

拷下擺


用於特薄至薄布料之針織T恤·內衣等之下擺或袖口拷縫

BLIND HEMMING

For hemming sleeves and bottoms of T-shirts or underwear etc. Applicable for light to extra light fabric.

特殊效果：上勾針改用LP231盲勾針·可以露出針線

Special effect : replace upper looper by blind looper,LP231, the needle thread can be shown on the surface.



選購配件 OPTIONAL DEVICE
VT, CSA, CSB, TUB



737K-504M2-04/LFC-3	1	3	-	4	0.7-2	3.6	6	DCX27#11	7000
747K-514M2-2□/LFC-3	2	4	2	4,5	0.7-2	3.6	6	DCX27#11	7000
747K-514M2-2□/ SMK	2	4	2	4,5	0.7-2	3.6	6	DCX27#11	7000
737K-504M2-04/TR	1	3	-	4	0.7-2	3.6	6	DCX27#11	7500
737K-504M2-04/TR/DKK□	1	3	-	4	0.7-2	3.6	6	DCX27#11	7500



747K-514M2-24/ SMK




747K-514M2-24/LFC-3




737K-504M2-04/TR



LFC-3



TR



鬆緊帶車縫

利用送帶裝置控制鬆緊帶之張力，適用於泳衣、內衣褲或運動服飾之鬆緊帶包縫

LFC-3：機械式送帶

多樣的壓腳可供選擇

SMK：電子計數式送帶

SMK1-A-01 附定位器，適合簡易伺服或離合器馬達

SMK1-A-02 以中繼線，連接伺服馬達

ELASTIC ATTACHING

Tape feeding device controls the tension. Applicable to swimming wear, underwear, sports wear's elastic band attaching.

LFC-3 : Mechanic type elastic tape feeding various presser feet for optional demand.

SMK: Electric metering type elastic tape feeding

SMK1-A-01 with synchronizer for simple servo motor or clutch motor

SMK1-A-02 Connected to servo motor by encoder cable

	壓具 Presser foot	鬆緊帶寬度 Band width	備註 Remark
737K	P216-3	2mm~13mm	標配 Standard
747K	P216-4	2mm~13mm	標配 Standard
	P217-4	Max. 20mm	選配 Optional
	P218-4	Max. 30mm	選配 Optional
	P219-4	Max. 35mm	選配 Optional

TR:簡易鬆緊帶車縫(浴帽車縫)

利用彈簧片調整，控制鬆緊帶之鬆緊程度，可簡易進行鬆緊帶之包縫，適用於不織布、塑膠布等浴帽或醫療用衣物
例如：浴帽、醫療用衣物等











TR:SIMPLE ELASTIC ATTACHING

For attaching elastic tape on non-woven or plastic cloth. The tension is controlled by spring.

Eg : Shower cap, medical clothing...etc.

選購配件 OPTIONAL DEVICE
EC, LFA, LS

K6

										
747K-514H4-24/GA	2	4	2	4	0.7-2	3.2	5.5	DCX27#11	7500	
757K-516H4-35/GA	2	5	3	5	0.7-2	3.6	6	DCX27#14	7000	
757K-516H4-55/GA	2	5	5	5	0.7-2	3.6	6	DCX27#14	7000	
747K-514H4-24/GA/DKK□	2	4	2	4	0.7-2	3.2	5.5	DCX27#11	7500	
757K-516H4-35/GA/DKK□	2	5	3	5	0.7-2	3.6	6	DCX27#14	7000	
757K-516H4-55/GA/DKK□	2	5	5	5	0.7-2	3.6	6	DCX27#14	7000	



747K-514H4-24/GA



757K-516H4-35/GA/CT



GA




GA/CT

折景車縫

適用中厚布料下層布間歇或連續性不規則折景車縫，可加滾邊喇叭增加車縫品質如裙子，床罩，窗簾等

注：P布條滾邊喇叭（入布寬度25mm，出布寬度6mm）



GATHERING

Continuous or intermittent random gathering on lower ply of medium fabric, can be equipped with piping folder to increase sewing quality for shirt, bed sheets, curtains etc.

Remark : P: Piping folder (tape width 25mm, finished size 6mm)

選購配件 OPTIONAL DEVICE
EC . P(KV57-A) , FG , VT ,CT , CSA , CSB , TUB

K7

										
手動 Manual	737K-504M5-04/BK(BK-1)	1	3	-	4	0.7-2	3.6	6	DCX27#11	7000
	747K-514M5-2□/BK(BK-1)	2	4	2	3,4	0.7-2	3.6	6	DCX27#11	7000
	747K-514M7-2□/BK(BK-1)	2	4	2	4,5	0.7-2	3.6	7	DCX27#11	7000
	737K-504M5-04/BK(BK-1)/DKK□	1	3	-	4	0.7-2	3.6	6	DCX27#11	7000
	747K-514M5-2□/BK(BK-1)/DKK□	2	4	2	3,4	0.7-2	3.6	6	DCX27#11	7000
	747K-514M7-2□/BK(BK-1)/DKK□	2	4	2	4,5	0.7-2	3.6	7	DCX27#11	7000
半自動 Semi-Auto	747K-514M5-23/BKS/DKK□	2	4	2	3	0.7-2	3.6	6	DCX27#11	7000
	747K-514M7-24/BKS/DKK□	2	4	2	4	0.7-2	3.6	7	DCX27#11	7000
簡易式全自動 Simplified Fully Auto	737K-504M5-04/ECB/BKT/DKK□	1	3	-	4	0.7-2	3.6	7	DCX27#11	7000
	747K-514M2-24/ECB/BKT/DKK□	2	4	2	4	0.7-2	3.6	7	DCX27#11	7000
全自動 Fully Auto	737K-504M5-0□/BKF	1	3	-	3,4,5	0.7-2	3.6	7	DCX27#11	7000
	747K-514M5-2□/BKF	2	4	2	3,4	0.7-2	3.6	7	DCX27#11	7000



737K-504M5-04/BK




747K-514M5-23/BKS



747L-514M-3-24/ECA/BKT



747K-514M5-23/BKF






線頭包縫

將線頭包入車縫線內，可防止縫合之開口處縫線脫落，適用於內衣褲、運動服之袖口及側邊縫合

BACK LATCHING SEAMING

To prevent seam looseness, turn over the thread and then insert into overlock seaming at the beginning of sewing. For sleeve and sideways sewing of underwear, sportswear etc.

操作 Operation	配件代號 Code	說明 Description	適用機頭 Applicable Series	驅動方式 Drive Type
手動 Manual	BK	Rotary Plate 	737K 747K 737L 747L	建議搭配伺服馬達，使用定針功能，提升車縫效率 To equip with servo motor for needle position function is optional and recommended.
	BK-1	Fixed Plate 		
半自動 Semi-Auto	BKS	4線拷克專用，針板舌自動伸縮 4 Thread overlock applicable, Needle plate tongue Auto-retracted	747K	腳踏板氣閥控制 氣動式 Pedal valve control Pneumatic type
簡易式全自動 Simplified Fully Auto	BKT	1. 簡易式，線頭長度約3cm 2. ECA切刀，針板有特殊風道設計，線頭向下吸回  1. Simplified type, back latch length 3cm. 2. With ECA cutter, Needle plate suction channel for thread-end down turning.	737K 747K 737L 747L	700K電控系統 氣動式 700K: Control system Pneumatic type
自動 Fully Auto	BKF	1. VT吸風切線 2. 可設定多種操作模式 3. 線頭側向吹回，長度可以調整(最短1cm) 1. With VT suction trimmer 2. Multi-operation mode setting 3. Thread-end side turning. Back latch length is adjustable (Min. 1cm)	737K 747K 737L 747L	賀欣 i70 直驅馬達 氣動式 Hohsing i70 Servo Motor Pneumatic type

K8



	2	4	2	4	0.7-2	3.6	7	DCX27#16	7500
747K-514M7-24	2	4	2	5	0.7-2	3.6	7	DCX27#16	7500
747K-514M7-25	2	5	5	6	0.7-2	3.6	6	DCX27#18	7500
747K-514M7-24/TG	2	4	2	4	0.7-2	3.6	7	DCX27#16	7500
747K-514M7-25/TG	2	4	2	5	0.7-2	3.6	7	DCX27#16	7500
747K-514M7-24/DKK□	2	4	2	4	0.7-2	3.6	7	DCX27#16	7500
747K-514M7-25/DKK□	2	4	2	5	0.7-2	3.6	7	DCX27#16	7500
747K-514M7-24/TG/DKK□	2	4	2	4	0.7-2	3.6	7	DCX27#16	7500
747K-514M7-25/TG/DKK□	2	4	2	5	0.7-2	3.6	7	DCX27#16	7500




747K-514M7-24



747K-514M7-24/TG/EC



757K-516X2-56



TG/EC


厚毛衣料肩帶包縫

適用於毛衣之肩部多包縫一條平織布條，可防止衣服肩部變形
注：布條裝置之導板使用，布條最大寬度為1/4"(6.35mm)

TAPE INSERTING ON BULKY KNITWEAR

For sewing a woven tape onto the shoulder of knitwear such as sweater, to prevent abnormal stretching.

Remark: Max. width of tape is 1/4"(6.35mm)



TG/EC 選購配件 OPTIONAL DEVICE

EC, AN, LFA, LS



514M7

厚毛衣料包縫

適用於粗厚毛線衣物車縫

OVER SEAMING ON BULKY KNITWEAR

For regular seaming on bulky knit fabric such as sweater.

514M7 選購配件 OPTIONAL DEVICE

AN, CT, CSA, CSB, TUB



516X2

薄牛仔包縫

特殊傳動行程結構適用於薄牛仔布料之包縫，例如：牛仔布 & 工作服

LIGHT DENIM OVERLOCK

Special driving mechanism for seaming on light denim fabric such as jeans, workwears etc.



516X2 選購配件 OPTIONAL DEVICE

CT, CSA, CSB, TUB

K9




	2	5	3	5	0.7-2	3.6	6	DCX27#14	7000
757K-516M2-35/PS	2	5	3	5	0.7-2	3.6	6	DCX27#14	7000
757K-516M2-55/PS	2	5	5	5	0.7-2	3.6	6	DCX27#14	7000
757K-401M2-50/TA	2	4	5	-	0.7-2	3.6	6	DCX27#14	7000
757K-516M2-35/PS/DKK□	2	5	3	5	0.7-2	3.6	6	DCX27#14	7000
757K-516M2-55/PS/DKK□	2	5	5	5	0.7-2	3.6	6	DCX27#14	7000
757K-401M2-50/TA/DKK□	2	4	5	-	0.7-2	3.6	6	DCX27#14	7000



757K-516M2-35/PS



757K-401M2-50/TA



PS



TA

口袋邊包縫

PS: 在褲袋邊緣多上一包邊布條，以強化縫合處，增加美觀
 注：標準喇叭之入布寬度為3/8”(9.5mm)

TA: 雙勾針機型，適用於褲袋邊緣加包邊布條，並車縫兩道環縫線以強化縫合處增加美觀
 注：標準喇叭(入布寬度25.4mm/出布寬度6.4mm)



POCKET BINDING

PS: To insert an extra tape to cover on the edge of pocket then by safety stitching for strengthening the pocket seaming. Suitable for high quality trousers.
 Remark: Standard folder for tape width is 3/8”(9.5mm)

TA: Two needle two chainstitches. Tape binding by two chainstitch on the edge of pocket of high quality trousers.
 Remark: Standard folder (tap width 25.4mm/finish width 6.4mm)

選購配件 OPTIONAL DEVICE
EC . FG

K10



	1	3	-	-	-	-	-	DCX27#11	7500
737K-WR/LFC-3	1	3	-	5	0.7-2	3.6	6	DCX27#14	7500
737K-504M3-05/PZ	1	2	-	-	0.7-2	3.6	5.5	DCX27#14	7000
757K-401M1/TW	1	3	-	5	0.7-2	3.6	6	DCX27#14	7500
737K-504M3-05/PZ/DKK□	1	2	-	-	0.7-2	3.6	5.5	DCX27#14	7000



737K-WR/LFC-3



737K-504M3-05/PZ



757K-401M1/TW




LFC-3

管狀布條車縫

將針織布條拷邊車縫後再反條成管形，適用於各種泳裝，睡衣或韻律服等管狀肩帶
 注：標準喇叭之布條入布寬度22mm(7/8") 成型之管狀布條直徑為5mm

SPAGHETTI SEWING

To sew knit fabric tape and turn over it into spaghetti tube for swimwears, nightgowns etc...
 Remark : Standard folder specification: tape width is 22mm (7/8") and the finished tube size is about 5mm in diameter.



選購配件 OPTIONAL DEVICE
FG



PZ

拉鍊包縫


適用於薄布料之拉鍊包縫，可將拉鍊與衣身裁片同時包縫

ZIP SEAMING

For regular seaming for zipper with light fabric.



選購配件 OPTIONAL DEVICE
VT, CSA, CSB, TUB



TW

毛巾布邊車縫

本機為單針單勾針機型，適用於毛巾布邊之車縫

TOWEL EDGING

This is a single needle, single looper machine, suitable for towel sewing.



選購配件 OPTIONAL DEVICE
CT, CSA, CSB, TUB